



HP Latex 375 Printer

Gain more unattended printing at lower cost of operation with this full-feature 1,63 m printer



Expand your applications – beat client expectations

- Get higher margins¹ printing on traditional signage substrates and beyond – even textiles² – up to 1,63 m.
- Reach more indoor spaces, like healthcare – water-based HP Latex Ink prints are odorless.²
- Enjoy efficient, automated double-sided banner printing.
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colours, and 1200 dpi.

Same-day delivery with more unattended production

- High quality at high speeds – 31 m²/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer.³
- Increase unattended printing with confidence – change 3 liter HP Latex Ink cartridges while the printer runs.
- Reach production speeds and avoid wait time – prints come out completely dry and ready to finish and deliver.
- You can minimise damage risk – scratch resistance is comparable to hard-solvent inks on SAV and PVC banner.⁴

Keep running costs low with 3 liter ink cartridges

- Help reduce your cost per print with cost-effective, 3 liter HP 871 Latex Ink Cartridges.¹
- Reduce time – HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic.⁵
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads.
- Monitor your printer remotely with the free HP Latex Mobile app.⁶

For more information, please visit <http://www.hp.com/go/latex375>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://hpllatexknowledgecenter.com/>

¹ For the HP Latex 375 Printer using cost-effective, high-capacity HP 871 3 liter Latex Ink Cartridges compared to the HP Latex 365 Printer using HP 831 775 ml Latex Ink Cartridges.

² Performance may vary depending on media – for more information, see <http://www.hp.com/go/mediasolutionslocator>. For best results, use textiles that do not stretch. The ink collector is required for porous textiles. Odorless prints: there is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ Banner-quality prints in outdoor (4-pass 4-colour) mode.

⁴ Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminates. Results may vary based on specific media performance.

⁵ ICC profiling with the spectrophotometer does not support uncoated textiles and backlights.

⁶ HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

Technical specifications

Print

Printing modes	91 m ² /hr - Max Speed (1 pass) 31 m ² /hr - Outdoor High Speed (4 pass) 23 m ² /hr - Outdoor Plus (6 pass) 17 m ² /hr - Indoor Quality (8 pass) 14 m ² /hr - Indoor High Quality (10 pass) 6 m ² /hr - Backkits, Textiles, and Canvas (15 pass) 5 m ² /hr - High Saturation Textiles (20 pass)
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	7 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimiser)
Cartridge size	3 L, 775 ml
Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimiser)
Long-term print-to-print repeatability	Average ≤ 1 dE2000, 95% of colours ≤ 2 dE2000 ¹

Media

Handling	Roll feed, take-up reel, automatic cutter (for vinyl, paper-based media, backlit polyester film)
Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, fabrics, mesh, textiles ²
Roll size	254 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Roll weight	42 kg
Roll diameter	250 mm
Thickness	Up to 0.5 mm

Applications

Banners; Displays; Double-sided banners; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Traffic signage

Connectivity

Interfaces	Gigabit Ethernet (1000Base-T)
------------	-------------------------------

Dimensions (w x d x h)

Printer	2561 x 840 x 1380 mm
Shipping	2795 x 760 x 1705 mm
Operating area	2761 x 1840 mm

Weight

Printer	231.5 kg
Shipping	333.5 kg

What's in the box

HP Latex 375 Printer; Printheads; Maintenance cartridge; Ink collector; Output platen protector; Printer stand; Spindle; Take-up reel; Variable front tension kit; Loading accessory; User maintenance kit; Edge holders; Quick reference guide; Setup poster; Documentation software; Power cords

Environmental ranges

Operating temperature	15 to 30°C
Operating humidity	20 to 80% RH (non-condensing)

Acoustics

Sound pressure	55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep)
Sound power	7.4 B(A) (operating), 5.7 B(A) (idle), <3.5 B(A) (sleep)

Power

Consumption	4.6 kW (printing), 85 W (ready), <2.5 W (sleep)
Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord

Certification

Safety	IEC 60950-1+A1+A2 compliant; EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC)
Electromagnetic	Compliant with Class A requirements, including EU (EMC Directive)
Environmental	CE marking compliant; ENERGY STAR®; EPEAT Bronze; EU RoHS; OSHA; REACH; RoHS Ukraine; RoHS Turkey; WEEE

Warranty

One-year limited hardware warranty

Ordering information

Product

V8NB3A	HP Latex 375 Printer
--------	----------------------

Accessories

F0M56A	HP Series 300 64-in Printer 2-in Spindle
F0M58A	HP Series 300 64-in Printer 3-in Spindle
F0M59A	HP Latex User Maintenance Kit
F0M64A	HP Series 300/500 Edge Holder Kit
T4E58B	HP Latex Media Saver Kit
T7U74A	HP Series 300/500 Ink Collector Foam Kit

Original HP printing supplies

CZ677A	HP 831 Cyan/Black Latex Printhead
CZ678A	HP 831 Yellow/Magenta Latex Printhead
CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead
CZ680A	HP 831 Latex Optimizer Printhead
CZ681A	HP 831 Latex Maintenance Cartridge
CZ694A	HP 831C 775-ml Black Latex Ink Cartridge
CZ695A	HP 831C 775-ml Cyan Latex Ink Cartridge
CZ696A	HP 831C 775-ml Magenta Latex Ink Cartridge
CZ697A	HP 831C 775-ml Yellow Latex Ink Cartridge
CZ698A	HP 831C 775-ml Light Cyan Latex Ink Cartridge
CZ699A	HP 831C 775-ml Light Magenta Latex Ink Cartridge
CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge
G0Y79C	HP 871C 3-liter Cyan Latex Ink Cartridge
G0Y80C	HP 871C 3-liter Magenta Latex Ink Cartridge
G0Y81C	HP 871C 3-liter Yellow Latex Ink Cartridge
G0Y82C	HP 871C 3-liter Black Latex Ink Cartridge
G0Y83C	HP 871C 3-liter Light Cyan Latex Ink Cartridge
G0Y84C	HP 871C 3-liter Light Magenta Latex Ink Cartridge
G0Y85A	HP 871 3-liter Latex Optimizer Cartridge

Original HP large format printing materials

HP Permanent Gloss Adhesive Vinyl (REACH certified)³
HP Backlit Polyester Film⁴
HP PVC-free Durable Smooth Wall Paper (REACH³, FSC⁵, UL GREENGUARD GOLD certified)⁶
HP Premium Poster Paper⁴ (FSC⁵ certified)⁶

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U9JF1E HP 2 year Next Business Day with Defective Media Retention
U9JF2E HP 3 year Next Business Day with Defective Media Retention
U9JF5PE HP 1 year Post Warranty Next Business Day with Defective Media Retention
U9JF6PE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

- Better for printing companies/operators – no special ventilation or HAPs¹
- Better for the end-customer, more differentiation – odorless prints reach more indoor spaces²
- Better for the environment – HP designs end-to-end sustainability into large-format printing
- HP Latex Inks are UL GREENGUARD GOLD Certified³

Please recycle printing hardware and eligible printing supplies. Find out how at our website:
<http://www.hp.com/ecosolutions>

¹ Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer – see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 31.1.

² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>.

⁴ Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

⁵ Performance may vary depending on media—for more information, see <http://www.hp.com/go/mediasolutionslocator>. For best results, use textiles that do not stretch. The optional ink collector is required for porous textiles.

⁶ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

⁷ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See <http://www.HPLFMedia.com/hp/ecosolutions> for details.

⁸ BMG Trademark license code FSC®-C115319, see <http://www.fsc.org>. HP trademark license code FSC®-C017543, see <http://www.fsc.org>. Not all FSC®-certified products are available in all regions.

⁹ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>.

